



# Safety Data Sheet

## NEXUS CORE CONV LAC FLAT 1G



### 1. Identification

<b>Product identifier</b>	NEXUS CORE CONV LAC FLAT 1G		
<b>Product code</b>	NXC-0710-1		
<b>Other means of identification</b>	N.Av.		
<b>Recommended use of the chemical and restrictions on use</b>	A protective and/or decorative finish or accompanying paint product. Not recommended for any other use not detailed on product data sheet or label.		
<b>Manufacturer</b>	GEMINI INDUSTRIES, INC. 2300 Holloway Drive El Reno, OK 73036 USA  Tel. 1-800-262-5710 Fax 1-405-262-9310 <a href="http://www.gemini-coatings.com/">http://www.gemini-coatings.com/</a>		
<b>Emergency phone number</b>	24-hour Emergency (Spill, Leak, Exposure or accident) INFOTRAC 800-535-5053 Outside USA, Call Collect 1-352-323-3500 (French & English)  HAZMAT Response and MSDS Help: EMI 800-510-8510		

### 2. Hazard identification

<b>Summary</b>	Highly flammable liquid and vapour. Keep away from heat, sparks and open flame. Avoid contact with skin, eyes and clothing. Do not breathe vapors. Do not ingest. If medical advice is needed, have this SDS or label at hand. Wear eye protection, gloves and other protective clothing that are adapted to the task being performed and the risks involved. P.S. The SIMDUT 2015/GHS hazards classification in this SDS is provided by the manufacturer using a Worst Case Scenario.
----------------	--

#### WHMIS 2015/GHS/OSHA HCS 2012

	Flammable liquids (Category 2) Skin corrosion/irritation (Category 2) Serious eye damage/eye irritation (Category 1) Germ cell mutagenicity (Category 1) Carcinogenicity (Category 1) Reproductive toxicity (Category 1) Specific target organ toxicity, single exposure (Category 3)
<b>DANGER</b> H225: Highly flammable liquid and vapour H318: Causes serious eye damage H350: May cause cancer H340: May cause genetic defects H360: May damage fertility or the unborn child H315: Causes skin irritation	

H336: May cause drowsiness or dizziness  
P201: Obtain special instructions before use.  
P202: Do not handle until all safety precautions have been read and understood.  
P210: Keep away from heat, sparks, open flames and other ignition sources. No smoking.  
P240: Ground or bond container and receiving equipment.  
P241: Use explosion-proof electrical, ventilating, lighting and all material-handling equipment.  
P242: Use only non-sparking tools.  
P243: Take precautionary measures against static discharge.  
P261: Avoid breathing vapours and spray.  
P264: Wash skin thoroughly after handling.  
P271: Use only outdoors or in a well-ventilated area.  
P280: Wear protective gloves, protective clothing and eye protection.  
P308+313: IF exposed or concerned: Get medical attention.  
P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P332+313: If skin irritation occurs: Get medical advice or attention.  
P304+340+P312: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.  
P305+351+338: IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.  
P310: Immediately call a physician.  
P362+364: Take off contaminated clothing and wash before reuse.  
P370+378: In case of fire: Use the National Fire Protection Association Class B extinguisher to extinguish.  
P403+P235+P233: Store in a well-ventilated place. Keep container tightly closed. Keep cool.  
P405: Store locked up.  
P501: Dispose of contents and container to a licensed chemical disposal agency in accordance with local, regional and national regulations.

### 3. Composition/information on ingredients

Common name	CAS	Weight % content
Butyl acetate (normal)	123-86-4	15 - 40 %
Ethyl alcohol	64-17-5	10 - 30 %
Nitrocellulose	9004-70-0	5 - 10 %
Urea, polymer with formaldehyde, isobutylated	68002-18-6	5 - 10 %
Xylene	1330-20-7	1 - 5 %
Isopropyl alcohol	67-63-0	1 - 5 %
Silica gel	112926-00-8	1 - 5 %
Isobutyl alcohol	78-83-1	1 - 5 %
n-Butyl alcohol	71-36-3	1 - 5 %
Methyl ethyl ketone	78-93-3	1 - 5 %
Propylene glycol monomethyl ether acetate	108-65-6	1 - 5 %
Solvent naphtha (petroleum), light aromatic (C8 to C10)	64742-95-6	1 - 5 %
Bis(2-Ethylhexyl) adipate	103-23-1	1 - 5 %
Ethylbenzene	100-41-4	0.1 - 1 %

**Note:** The manufacturer withholds the actual concentration range of the ingredients as a trade secret.

## 4. First-aid measures

<b>Inhalation</b>	Move person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen by trained personnel. If a problem develops or persists, seek medical attention.
<b>Skin contact</b>	Wash skin with warm water and mild soap for at least 15 minutes. Remove contaminated clothing and wash before reuse. Avoid touching eyes with contaminated body parts. If a problem develops or persists, seek medical attention.
<b>Eye contact</b>	IMMEDIATELY! Flush with water for at least 15 minutes. Remove contact lenses if easy to do. Hold eyelids apart to rinse properly. Seek medical attention immediately.
<b>Ingestion</b>	DO NOT induce vomiting, unless recommended by medical personnel. Never give anything by mouth if victim is unconscious or convulsing. If victim is conscious wash out mouth with water and give 1-2 glasses of water to drink. If spontaneous vomiting occurs, keep head below hip level to prevent aspiration into the lungs. Seek medical attention or contact a Poison Centre immediately.
<b>Other</b>	No information available.
<b>Symptoms</b>	May cause severe eye irritation or eye damage. May cause redness, dryness, rash and skin irritation. Overexposure may cause headache, dizziness and nausea.
<b>Notes to the physician</b>	Treat symptomatically. If gastric lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

## 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Dry chemicals, chemical foam, carbon dioxide (CO <sub>2</sub> ), class B extinguisher. Do not use a heavy water jet.
<b>Specific hazards arising from the chemical</b>	Highly flammable liquid and vapour. Vapours are heavier than air and may travel to an ignition source distant from the material handling point. May be ignited by heat, sparks, flame or static electricity. Do not apply to hot surfaces.
<b>Special protective equipment</b>	Firefighters must wear self contained breathing apparatus with full face mask. Firefighting suit may not be efficient against chemicals.
<b>Special protective actions for fire-fighters</b>	Use water spray to cool fire-exposed containers. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Do not touch spilled material. Make sure to wear personal protective equipment mentioned in this Safety Data Sheet.
<b>Environmental precautions</b>	Prevent entry into sewers, closed areas and release to the environment. For a large spill, consult the Department of Environment or the relevant authorities.
<b>Methods and materials for containment and cleaning up</b>	Remove sources of ignition. Ventilate the area well. Absorb with inert material (soil, sand, vermiculite) and place in an appropriate waste disposal clearly identified. Use non-sparking and antistatic tools. Dispose via a licensed waste disposal contractor. Finish cleaning the contaminated surface by rinsing with soapy water.

## 7. Handling and storage

<b>Precautions for safe handling</b>	Keep away from heat, sparks and open flame. Turn off all pilot lights, flames, stoves, heaters, electric motors, welding equipment and other sources of ignition. Use non-sparking and antistatic tools. Use only in well ventilated area. Do not breathe vapors. Avoid contact with skin, eyes and clothing. Wear eye protection, gloves and other protective clothing that are adapted to the task being performed and the risks involved. Keep containers tightly closed when not in use. Keep containers tightly closed when not in use. Wash hands, forearms and face thoroughly after handling this compound and before eating, drinking or using toiletries. Remove contaminated clothing and wash before reuse.
<b>Conditions for safe storage, including any incompatibilities</b>	Storage and handling should follow the NFPA 30 Flammable and/or Combustible Liquids Code and the National Fire Code of Canada (NFCC). Store tightly closed and in properly labelled container in a dry, cool and well ventilated place. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store away from oxidizing materials and incompatible materials (see section 10). Keep away from direct sunlight and heat.
<b>Storage temperature</b>	10 to 25°C (50 to 77°F)

## 8. Exposure controls/personal protection

<b>Immediately Dangerous to Life or Health</b>	N-Butyl acetate: 1700 ppm. Ethyl alcohol: 3300 ppm. Xylenes: 900 ppm. Isopropyl alcohol: 2000 ppm. Silica - Amorphous, gel: 3000 mg/m <sup>3</sup> . Isobutyl alcohol: 1600 ppm. Methyl ethyl ketone: 3000 ppm. Ethylbenzene: 800 ppm. n-Butyl Alcohol: 1400 ppm.			
Butyl acetate (normal)	STEL	200 ppm		ACGIH , ON
		200 ppm	950 mg/m <sup>3</sup>	RSST
	TWA (8h)	20 ppm		BC
		150 ppm		ACGIH , ON
		150 ppm	713 mg/m <sup>3</sup>	RSST
Ethyl alcohol	STEL	1000 ppm		ACGIH , BC, ON
	TWA (8h)	1000 ppm	1880 mg/m <sup>3</sup>	RSST
Isopropyl alcohol	STEL	400 ppm		ACGIH , BC, ON
		500 ppm	1230 mg/m <sup>3</sup>	RSST
	TWA (8h)	200 ppm		ACGIH , BC, ON
		400 ppm	983 mg/m <sup>3</sup>	RSST
Xylene	STEL	150 ppm		ACGIH , BC, ON
		150 ppm	651 mg/m <sup>3</sup>	RSST
	TWA (8h)	100 ppm		ACGIH , BC, ON
		100 ppm	435 mg/m <sup>3</sup>	RSST
Methyl ethyl ketone	STEL	100 ppm		BC
		100 ppm	300 mg/m <sup>3</sup>	RSST
		300 ppm		ACGIH , ON
	TWA (8h)	50 ppm		BC
		50 ppm	150 mg/m <sup>3</sup>	RSST
		200 ppm		ACGIH , ON
Propylene glycol monomethyl ether acetate	STEL	75 ppm		BC
	TWA (8h)	50 ppm		BC , US AIHA
		50 ppm	270 mg/m <sup>3</sup>	ON
n-Butyl alcohol	Ceiling	30 ppm		BC
		50 ppm	152 mg/m <sup>3</sup>	RSST (Pc, RP)
	TWA (8h)	15 ppm		BC

Silica gel	TWA (8h)	Respirable Dust	20 ppm	1.5 mg/m <sup>3</sup>	ACGIH , ON
		Total Dust		4 mg/m <sup>3</sup>	BC
		Respirable Dust		6 mg/m <sup>3</sup>	BC
		Total Dust		10 mg/m <sup>3</sup>	RSST
Isobutyl alcohol	TWA (8h)		50 ppm		ACGIH , ON
			50 ppm	152 mg/m <sup>3</sup>	ACGIH , BC, ON
Ethylbenzene	TWA (8h)	STEL	125 ppm	543 mg/m <sup>3</sup>	RSST
			20 ppm		ACGIH , BC, ON
			100 ppm	434 mg/m <sup>3</sup>	RSST
<b>Appropriate engineering controls</b>	Provide sufficient mechanical ventilation (general or local exhaust) to keep the airborne concentrations of vapours, mists, aerosols or dust below their respective occupational exposure limits.				
<b>Individual protection measures</b>					
<b>Eye</b>	In the workplace, wear safety glasses with side shields. If risk of contact with eyes or/and the face wear chemical splash goggles and/or a face shield.				
<b>Hands</b>	Wear nitrile or neoprene gloves. Before using, user should confirm impermeability. Discard gloves with tears, pinholes, or signs of wear. Gloves must only be worn on clean hands.				
<b>Skin</b>	Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Wear normal work clothing covering arms and legs as required by employer code. If necessary, wear an apron or long-sleeve protective coverall suit.				
<b>Respiratory</b>	Respiratory protection is not required for normal use. Where the conditions in the workplace require a respirator, it is necessary to follow a respiratory protection program. Moreover, respiratory protection equipment (RPE) must be selected, fitted, maintained and inspected in accordance with regulations and standard 29 CFR 1910.134 (OSHA), ANSI Z88.2 or CSA Z 94.11 (Canada) and approved by NIOSH/MSHA. In case of insufficient ventilation or in confined or enclosed space and for an assigned protection factor (APF) up to 10 times the exposure limit, wear a half mask respirator with organic vapour cartridges fitted with P100 filters. For an APF until maximum 100 times of exposure limit, wear a full face respirator mask with organic vapour cartridges and P100 filters.				
<b>Feet</b>	Wear rubber boots to clean up a spill.				

## 9. Physical and chemical properties

<b>Physical state</b>	Liquid	<b>Flammability</b>	Flammable
<b>Colour</b>	Coloured	<b>Flammability limits</b>	N/Av.
<b>Odour</b>	Solvent	<b>Flash point</b>	-4°C (24.8°F)
<b>Odour threshold</b>	N/Av.	<b>Auto-ignition temperature</b>	170°C (338°F)
<b>pH</b>	N/Av.	<b>Sensibility to electrostatic charges</b>	Yes
<b>Melting point</b>	N/Av.	<b>Sensibility to sparks and/or friction</b>	No
<b>Freezing point</b>	N/Av.	<b>Vapour density</b>	>1 (Air = 1)
<b>Boiling point</b>	78 to 214°C (172.4 to 417.2°F)	<b>Relative density</b>	0.9436 kg/L (Water = 1)
<b>Solubility</b>	Negligible (<25%) in water	<b>Partition coefficient n-octanol/water</b>	N/Av.
<b>Evaporation rate</b>	> Butyl Acetate	<b>Decomposition temperature</b>	N/Av.

<b>Vapour pressure</b>	N/Av.	<b>Viscosity</b>	N/Av.
<b>Percent Volatile</b>	67.67%	<b>Molecular mass</b>	N/Av.
N/Av.: Not Available    N/Av.: Not Applicable    Und.: Undetermined    N/E: Not Established			

## 10. Stability and reactivity

<b>Reactivity</b>	No reactivity expected.
<b>Chemical stability</b>	Stable under recommended storage conditions.
<b>Possibility of hazardous reactions (including polymerizations)</b>	A dangerous reaction will not occur.
<b>Conditions to avoid</b>	Avoid heat, flame and sparks. Avoid contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents (e.g. chlorine, fluorine, nitric acid, perchloric acid, peroxides, nitrates, chlorates, chromates, permanganates and perchlorates), strong acids (e.g. hydrochloric acid, sulfuric acid, phosphoric acid), strong bases (e.g. hydroxides, solutions of ammonia, amines, carbonates).
<b>Hazardous decomposition products</b>	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## 11. Toxicological information

<b>Numerical measures of toxicity</b>	Butyl acetate (normal)	Ingestion	10768 mg/kg	Rat	LD50
		Inhalation	>32.5 mg/l/4h	Rat	LC50
		Skin	>17600 mg/kg	Rabbit	LD50
	Ethyl alcohol	Ingestion	7060 mg/kg	Rat	LD50
		Inhalation	39 mg/l/4h	Mouse	LC50
		Skin	20000 mg/kg	Rabbit	LD50
	Nitrocellulose	Ingestion	>5000 mg/kg	Rat	LD50
		Ingestion	>5000 mg/kg	Rat	LD50
	Urea, polymer with formaldehyde, isobutylated	Skin	>5000 mg/kg	Rabbit	LD50
		Ingestion	8532 mg/kg	Rat	LD50
		Inhalation	28.7 mg/l/4h	Rat	LC50
	Propylene glycol monomethyl ether acetate	Skin	>5000 mg/kg	Rabbit	LD50
		Ingestion	9100 mg/kg	Rat	LD50
		Inhalation	>5.7 mg/l/4h	Rat	LC50
	Bis(2-Ethylhexyl) adipate	Skin	17297 mg/kg	Rabbit	LD50
		Ingestion	790 mg/kg	Rat	LD50
		Inhalation	24.2 mg/l/4h	Rat	LC50
	n-Butyl alcohol	Skin	3400 mg/kg	Rabbit	LD50
		Ingestion	2460 mg/kg	Rat	LD50
		Inhalation	19.2 mg/l/4h	Rat	LC50
	Isobutyl alcohol	Skin	3400 mg/kg	Rabbit	LD50
		Ingestion	5045 mg/kg	Rat	LD50
		Inhalation	66.1 mg/l/4h	Rat	LC50
	Isopropyl alcohol	Skin	6280 mg/kg	Rat	LD50
Ingestion		3160 mg/kg	Rat	LD50	
Inhalation		>2.08 mg/l/4h	Rat	LC50	
Silica gel	Skin	>2000 mg/kg	Rabbit	LD50	
	Ingestion	2737 mg/kg	Rat	LD50	
	Inhalation	32.5 mg/l/4h	Rat	LC50	
Methyl ethyl ketone	Ingestion	2737 mg/kg	Rat	LD50	
	Inhalation	32.5 mg/l/4h	Rat	LC50	

		<p>Skin 6480 mg/kg Rabbit LD50</p> <p>Ingestion 8400 mg/kg Rat LD50</p> <p>Inhalation &gt;5.2 mg/l/4h Rat LC50</p> <p>Skin &gt;3750 mg/kg Rabbit LD50</p> <p>Ingestion 3523 mg/kg Rat LD50</p> <p>Inhalation 27.6 mg/l/4h Rat LC50</p> <p>Skin 3200 mg/kg Rabbit LD50</p> <p>Ingestion 3500 mg/kg Rat LD50</p> <p>Inhalation 17.3 mg/l/4h Rat LC50</p> <p>Skin 15380 mg/kg Rabbit LD50</p>
	Solvent naphtha (petroleum), light aromatic (C8 to C10)	
	Xylene	
	Ethylbenzene	
<b>Likely routes of exposure</b>	Skin, eyes, inhalation.	
<b>Delayed, immediate and chronic effects</b>	<b>Eye contact</b>	May cause severe eye irritation or eye damage. Eye Irritation/Corrosion, Rabbit (OECD TG 405): tests performed separately with each ingredient of this mixture gave from mild irritating to corrosive results.
	<b>Skin contact</b>	May cause redness, dryness, rash and skin irritation. Skin Irritation/Corrosion, Rabbit (OECD 404) : tests performed with each ingredient of this mixture gave not irritating to irritating results.
	<b>Inhalation</b>	Excessive inhalation is harmful. Inhalation of vapours may cause central nervous system depression such as drowsiness, headache, dizziness, vertigo, nausea and fatigue. The severity of symptoms may vary depending on exposure conditions. Prolonged and repeated exposure may cause damage to central nervous system.
	<b>Ingestion</b>	Ingestion can cause abdominal pain, nausea, cramps, headache, dizziness, diarrhea and vomiting.
	<b>Respiratory or skin sensitization</b>	Ingredients present at levels greater than or equal to 0.1% of this product are not skin or respiratory sensitizers.
	<b>IARC/NTP Classification</b>	<b>Common name IARC NTP</b> Ethylbenzene 2B - IARC : 1- Carcinogenic; 2A- Probably carcinogenic; 2B- Possibly carcinogenic. NTP : K- Known to be carcinogens; R- Reasonably anticipated to be carcinogens.
	<b>Carcinogenicity</b>	Contains an ingredient possibly carcinogenic to humans (Group 2B, IARC). In the absence of specific test data, the classification of the mixture solvent naphtha (petroleum), light aromatic (C8-C10) (CAS No. 64742-95-6) should be determined based on the levels of benzene (CAS no. 71-43-2). This classification may not apply if it can be shown that the chemical contains less than 0.1 % w/w benzene. Benzene (CAS no 71-43-2) is carcinogenic to humans. The risk of cancer depends on duration and level of exposure. There is sufficient evidence for the carcinogenicity of alcoholic (Ethanol) beverages in humans (IARC). The occurrence of malignant tumors of the oral cavity, pharynx, larynx, oesophagus, liver, breast and colorectal is causally related to the excessive consumption of alcoholic beverages. Ethanol when not consumed in an alcoholic beverage is not classifiable as a human carcinogen.
	<b>Mutagenicity</b>	Contains potential mutagen ingredient. In the absence of specific test data, the classification of the mixture solvent naphtha (petroleum), light aromatic (C8-C10) (CAS No. 64742-95-6) should be determined based on the levels of benzene (CAS no. 71-43-2). This classification may not apply if it can be shown that the chemical contains less than 0.1 % w/w benzene. Benzene (CAS no 71-43-2) is carcinogenic to humans.
	<b>Reproductive toxicity</b>	Major malformations have been reported in infants born of women who had been working with solvent-based paints (oil-based paints) during pregnancy. Therefore, long-term exposure to solvent-based paints that may occur in occupational life can affect a developing baby (American Journal of Industrial Medicine, 1980). Xylene (CAS no 1330-20-7) overexposure may affect fetal development in laboratory animals by inhalation during pregnancy. Studies in humans and especially in animals are indicative that ingestion of high doses of ethanol (CAS no 64-17-5), as alcoholic beverage, can affect male and female fertility.
	<b>Specific target organ toxicity - single exposure</b>	Central nervous system.  No target organ is listed.

	<b>Specific target organ toxicity - repeated exposure</b>
<b>Interactive effects</b>	No information available for this product.
<b>Other information</b>	The oral and skin acute toxicity estimates (ATE) of the mixture were calculated to be greater than 2000 mg/kg. The acute toxicity estimates (ATE) by inhalation of the mixture were calculated to be greater than 20 mg/L/4h for vapours and to be greater than 5 mg/L/4h for the aerosols and mists. These values are not classified according to WHMIS 2015 and OSHA HCS 2012.


## 12. Ecological information

<b>Ecological toxicity</b>	Aquatic Invertebrate - Daphnia magna	EC50	44 mg/L; 48 h (CAS no 123-86-4)
	Fish - Pimephales promelas - Fresh water	LC50	18 mg/L; 96 h (CAS no 123-86-4) OECD 203
	Algae - Desmodesmus subspicatus	EC50	674.7 mg/L; 72 h (CAS no 123-86-4) OECD 201
	Fish - Pimephales promelas [flow-through]	LC50	13400-15100 mg/L; 96 h (CAS no 64-17-5)
	Aquatic Invertebrate - Daphnia magna	EC50	9268-14221 mg/L; 48 h (CAS no 64-17-5)
	Algae, Pseudokirchneriella subcapitata	EC50	579 mg/L; 96 h (Nitrocellulose)
	Fish - Oncorhynchus mykiss - Rainbow trout	LC50	13.5-17.3 mg/L; 96 h (CAS no 1330-20-7)
	Aquatic Invertebrate - Daphnia magna	EC50	1.3-3.7 mg/L; 48 h (CAS no 1330-20-7)
	Fish - Fathead minnow, Pimephales promelas - fresh water	LC50	9640 mg/L; 96h (CAS no 67-63-0)
	Aquatic Invertebrate - Crustaceans, Daphnia Magna	EC50	3644 mg/L; 48 h (CAS no 67-63-0)
	Fish - Pimephales promelas - Fresh water	LC50	1370-1670 mg/L; 96 h (CAS no 78-83-1)
	Aquatic Invertebrate - Daphnia magna	EC50	1300 mg/L; 48 h (CAS no 78-83-1)
	Fish - Pimephales promelas [static]	LC50	1376 mg/L; 96h (CAS no 71-36-3) OEDC 203
	Aquatic Invertebrate - Daphnia magna	EC50	1983 mg/L; 48h (CAS no 71-36-3) OEDC 202
	Fish - Fathead minnow, Pimephales promelas - fresh water	LC50	3600 mg/L; 96 hr (CAS no 78-93-3)
	Aquatic Invertebrate - Daphnia magna	EC50	5091 mg/L; 48 hr (CAS no 78-93-3)
	Fish - Oncorhynchus mykiss - Rainbow trout	LC50	100-180 mg/L; 96h (CAS no 108-65-6) OECD 203
	Aquatic Invertebrate - Daphnia magna	EC50	>500 mg/L; 48 h (CAS no 108-65-6)
	Fish - Oncorhynchus mykiss - Rainbow trout	LC50	9.2 mg/L ; 96h (CAS no 64742-95-6)
	Aquatic Invertebrate - Daphnia Magna, Water flea, fresh water	EC50	6.14 mg/L ; 48h (CAS no 64742-95-6)
Fish - Lepomis macrochirus [static]	LC50	0.48-0.85 mg/L; 96 h (CAS no 103-23-1)	
Aquatic Invertebrate - Daphnia Magna (fresh water)	EC50	>1.6 mg/L; 48 h (CAS no 103-23-1)	
<b>Persistence</b>	Contains an or many ingredients that may be persistent in aquatic environment.		




<b>Degradability</b>	The product is a mixture of which some ingredients are readily biodegradable (> 60% in 28 days) while other ingredients are not readily biodegradable (<60% in 28 days).
<b>Bioaccumulative potential</b>	The product is a mixture of which some ingredients have a low bioaccumulation potential (Log Kow of <3 and / or BCF <500) while other ingredients have some potential to bioaccumulate (Log Kow of >3 and / or BCF >500).
<b>Mobility in soil</b>	The product is a mixture of which some ingredients evaporate very easily from the surface of the soil. Moreover, some ingredients have very high mobility in soil, while other ingredients have moderate to low mobility in soil.
<b>Other adverse effects</b>	This chemical does not deplete the ozone layer.

### 13. Disposal considerations

<b>Container</b> 	Important! Prevent waste generation. Use in full. DO NOT dispose residue in sewers, streams or drinking water supply. DO NOT pierce, cut, heat, or burn the container, even after use. Paint residues, including lacquers, dyes, shellacs, varnishes, paint solvents and thinners, can be reprocessed where there is a recovery program. Residues and empty containers must be considered as hazardous waste. Dispose via a licensed waste disposal contractor. Observe all federal, state/provincial and municipal regulations. If necessary consult the Department of Environment or the relevant authorities.
--	--

### 14. Transport information

<b>UN Number</b>	UN 1263
<b>UN Proper Shipping Name</b>	PAINT
<b>Environmental hazards</b>	This material does not contain marine pollutant.
<b>Special precautions for user</b>	Permit required for transportation with proper DANGER placards displayed on vehicle.
<b>TDG - Transportation of Dangerous Goods (Canada)</b>	
<b>Transport hazard class(es)</b>	 Class 3
<b>Packing group</b>	II
<b>IMO/IMDG - International Maritime Transport</b>	
<b>Classification</b>	UN 1263. PAINT. Class 3, PG II. Emergency schedules (EmS-No) F-E, S-E
<b>IATA - International Air Transport Association</b>	
<b>Classification</b>	UN 1263. PAINT. Class 3, PG II.
<small>These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. In addition, if a domestic exemption exists, it is the responsibility of the shipper to define the application of it.</small>	

## 15. Regulatory information

### CANADA

Common name	CAS	CEPA	DSL	NDSL	NPRI
Butyl acetate (normal)	123-86-4	X	X		X
Ethyl alcohol	64-17-5	X	X		X
Nitrocellulose	9004-70-0		X		
Urea, polymer with formaldehyde, isobutylated	68002-18-6		X		
Xylene	1330-20-7	X	X		X
Isopropyl alcohol	67-63-0	X	X		X
Silica gel	112926-00-8		X		
Isobutyl alcohol	78-83-1	X	X		X
n-Butyl alcohol	71-36-3	X	X		X
Methyl ethyl ketone	78-93-3	X	X		X
Propylene glycol monomethyl ether acetate	108-65-6	X	X		X
Solvent naphtha (petroleum), light aromatic (C8 to C10)	64742-95-6	X	X		X
Bis(2-Ethylhexyl) adipate	103-23-1		X		X
Ethylbenzene	100-41-4	X	X		X

- CEPA: List of Toxic Substances Managed Under Canadian Environmental Protection Act

- DSL: Domestic Substances List Inventory

- NDSL: Non-Domestic Substances List Inventory

- NPRI: National Pollutant Release Inventory Substances

### UNITED STATE OF AMERICA

Common name	CAS	TSCA	CER CLA	EPCRA 313	EPCRA 302/304	CAA 112(b) HON	CAA 112(b) HAP	CAA 112(r)	CWA 311	CWA Prio.
Butyl acetate (normal)	123-86-4	X	X						X	
Ethyl alcohol	64-17-5	X								
Nitrocellulose	9004-70-0	X								
Urea, polymer with formaldehyde, isobutylated	68002-18-6	X								
Xylene	1330-20-7	X	X	X		X	X		X	
Isopropyl alcohol	67-63-0	X		X						
Silica gel	112926-00-8	X								
Isobutyl alcohol	78-83-1	X	X							
n-Butyl alcohol	71-36-3	X	X	X					X	
Methyl ethyl ketone	78-93-3	X	X	X		X	X			
Propylene glycol monomethyl ether acetate	108-65-6	X								
Solvent naphtha (petroleum), light aromatic (C8 to C10)	64742-95-6	X								
Bis(2-Ethylhexyl) adipate	103-23-1	X								
Ethylbenzene	100-41-4	X	X	X		X	X		X	X

- TSCA: Toxic Substance Control Act

- CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act list of hazardous substances

- EPCRA 313: Emergency Planning and Community Right-to-Know Act, Section 313 Toxic Chemicals

- EPCRA 302/304: Emergency Planning and Community Right-to-Know Act, Section 302/304 Extremely Hazardous Substances

- CAA 112(b) HON: Clean Air Act - Hazardous Organic National Emission Standard for Hazardous Air Pollutant


- CAA 112(b) HAP: Clean Air Act - Hazardous Air Pollutants lists pollutants

- CAA 112(r): Clean Air Act - Regulated Chemicals for Accidental Release Prevention

- CWA 311: Clean Water Act - List of Hazardous Substances
- CWA Priority: Clean Water Act - Priority Pollutant list

### California Proposition 65

Common name	CAS	Cancer	Reproductive and Developmental Toxicity
Ethyl alcohol	64-17-5	X	X
Ethylbenzene	100-41-4	X	

<b>Other regulations</b>								
	<div style="display: flex; justify-content: space-around; align-items: flex-start;"> <div style="text-align: center;"> <p><b>HMIS</b></p> <table border="1" style="border-collapse: collapse; width: 100px;"> <tr><td style="background-color: blue; color: white;">●</td><td>Health</td></tr> <tr><td style="background-color: red; color: white;">●</td><td>Flamability</td></tr> <tr><td style="background-color: yellow; color: black;">●</td><td>Reactivity</td></tr> <tr><td style="border: 1px solid black;">○</td><td>Protective Equipment</td></tr> </table> </div> <div style="text-align: center;"> <p><b>NFPA</b></p>  </div> </div>	●	Health	●	Flamability	●	Reactivity	○
●	Health							
●	Flamability							
●	Reactivity							
○	Protective Equipment							

## 16. Other information

<b>Date (YYYY-MM-DD)</b>	GEMINI INDUSTRIES, INC. 2019-09-19
<b>Version</b>	01
<b>Other information</b>	<p>- The GHS hazards classification in this SDS is from the original SDS provided by the manufacturer.</p> <p>REFERENCES:</p> <ul style="list-style-type: none"> <li>- Haz-Map, Information on Hazardous Chemicals and Occupational Diseases, <a href="http://hazmap.nlm.nih.gov/index.php">http://hazmap.nlm.nih.gov/index.php</a></li> <li>- Service du répertoire toxicologique de la Commission des normes, de l'équité, de la santé et de la sécurité du travail (CNESST), <a href="http://www.reptox.csst.qc.ca">http://www.reptox.csst.qc.ca</a></li> <li>- TOXNET Databases, Toxicology Data Network, NIH U.S. National Library of Medicine, <a href="http://toxnet.nlm.nih.gov/">http://toxnet.nlm.nih.gov/</a></li> <li>- NIOSH Pocket Guide to Chemical Hazards, Centers for Disease Control and Prevention, NIOSH Publications, 2007, <a href="http://www.cdc.gov/niosh/npg/npg.html">http://www.cdc.gov/niosh/npg/npg.html</a></li> <li>- The National Center for Biotechnology Information, National Institutes of Health (NIH), U.S. National Library of Medicine, <a href="http://pubchem.ncbi.nlm.nih.gov/search/">pubchem.ncbi.nlm.nih.gov/search/</a></li> </ul> <p>ACGIH: American Conference of Governmental Industrial Hygienists            AIHA: American Industrial Hygiene Association            HMIS: Hazardous Materials Identification System            NFPA: National Fire Protection Association            OSHA: Occupational Safety and Health Administration (USA)            NIOSH: National Institute for Occupational Safety and Health            NTP: National Toxicology Program            RSST: Règlement sur la santé et la sécurité du travail (Québec)            GHS: Globally Harmonized System            IARC: International Agency for Research on Cancer            IDLH: Immediately Dangerous to Life or Health            STEL: Short Term Exposure Limit (15 min)            TWA: Time Weighted Averages            WHMIS: Workplace Hazardous Materials Information System</p> <p>To the best of our knowledge, the information contained herein is accurate. However, neither Prilux System nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.</p>