



PRODUCT DATA SHEET

Universal Primer Stain Blocking Additive

DESCRIPTION

ESB2 has been designed to be added to UP-1000 Universal Primer as an additional step in limiting bleed through of stains and tannins on new wood. For addition to UP-1000 Universal Primer only.

PRODUCT NUMBERS / SHEENS	COATING PROPERTIES	PREPARATION INSTRUCTIONS
ESB2	<p>Viscosity: 17-22 #2 ZAHN Weight Solids: 38.5% Volume Solids: 17.3% Weight/Gallon: 11.2 lbs./gal</p> <p>VOC (reg./coating): .00 lbs./gl. or 0.0 g/l VOC (act/material): 0.0 lbs./gl. or 0.0 g/l VOC Ratio: 0.0 lbs. VOC/lbs. Solids HAPS Ratio: 0.0 lbs. HAPS/lbs. Solids</p>	<p>How To Use : ESB2 has been designed to be used with Universal Primer, UP-1000 only. Do not add to any other products. For gallon containers-Add 5 oz of ESB2 per gallon of UP-1000*. For 5 gallon pails. Add 25 oz of ESB2 per Pail of UP-1000*. *Shake immediately after adding ESB2 to the UP-1000!</p> <p>Max VOC after addition of ESB2 at recommended amount is <275 gpl.</p> <p>Pot life: The UP-1000 will have 2 weeks of pot life after the addition of ESB2. Note: Viscosity will increase slightly every few days. Product may require a small reduction at times with water to achieve the desired spray viscosity. Typically no more than 5% by volume of additional water is necessary.</p> <p>Mixing Instructions: Add the proper amount of ESB2 to the container of UP-1000 and <u>immediately mix</u> by placing in a commercial paint shaker or incorporate with a propeller blade mixer for a <i>minimum</i> of 5 minutes.</p> <p>Important Note! Mix immediately once the ESB2 has been added. Do NOT let the mixture sit without mixing.</p> <p>Approved Companion Products UP-1000</p>
PRODUCT ADVANTAGES		
<ul style="list-style-type: none"> ➤ Provides Additional Stain And Tannin Blocking Properties For UP-1000 Universal Primer ➤ Mixes In Easily With A Shaker Or Mixing Blade ➤ Zero VOC ➤ Zero HAPs 		
	<p><i>Note: These numbers represent actual control values on a smooth, sanded substrate. Spray techniques, texture, and sealing as well as film thickness may give different results on actual work, but they may be used for comparison. To the best of our knowledge, the above technical data is true and accurate at the date of issuance but is subject to change without prior notice.</i></p>	

September, 2024

The following supersedes any provision contained in the forms, letters and papers of your company. This product is designed and intended for professional application only. All products should be thoroughly tested under application conditions prior to use. The information contained herein is believed to be reliable. **HOWEVER, GEMINI MAKES NO WARRANTY CONCERNING THIS PRODUCT, WHETHER EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** UNDER NO CIRCUMSTANCES SHALL GEMINI BE LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR ANY OTHER DAMAGES FROM ALLEGED NEGLIGENCE, BREACH OF WARRANTY, STRICT LIABILITY, OR ANY OTHER LEGAL THEORY, ARISING OUT OF THE USE OR HANDLING OF THIS PRODUCT. THE SOLE REMEDY OF THE BUYER AND THE SOLE LIABILITY OF GEMINI FOR ANY CLAIMS SHALL BE LIMITED TO THE BUYER'S PURCHASE PRICE OF THE PRODUCT WHICH IS THE SUBJECT OF THE CLAIM OR THE AMOUNT ACTUALLY PAID FOR SUCH PRODUCT, WHICHEVER IS LESS. TECHNICAL ADVICE FURNISHED BY GEMINI SHALL NOT CONSTITUTE AN EXPRESS WARRANTY, WHICH IS EXPRESSLY DISCLAIMED. ALL TECHNICAL ADVICE GIVEN IS ACCEPTED AT THE RISK OF THE BUYER. **CAUTION: DANGER! FLAMMABLE! VAPORS MAY CAUSE FLASH FIRE. VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED. INJURIOUS TO EYES. KEEP OUT OF THE REACH OF CHILDREN!** BEFORE using this product it is essential that the "Material Safety Data Sheet" describing the product as well as the "Product Label" be reviewed. If your company does not have such information or has any questions, contact the manufacturer.